

M & M Precision, Penn State & NIST Team Up For Gear Metrology Research

In 1993, M & M Precision Systems was awarded a three-year, partial grant from the Advanced Technology Program of the Department of Commerce's National Institute of Standards and Technology (NIST). Working with Pennsylvania State University, M&M embarked on a technology development project to advance gear measurement capabilities to levels of accuracy never before achieved.

Responding to industry concerns about the measurement uncertainties associated with gear manufacturing process control and the competitive position of U.S. gear manufacturers worldwide, M & M contributed over \$1 million of its own funds to significantly improve gear measurement accuracies and provide a proven methodology for verifying these accuracies.

Project Goals

The goals of the project included:

- Develop and implement a rational methodology for analytically representing all points on the running surfaces of all teeth on a generic gear, necessary information for transmission error prediction, analysis of heat treat distortion, etc.;

- Model the accuracy of generative gear measurement

machines as a function of accuracy of the components of the system;

- Determine the accuracy of state-of-the-art generative gear measurement machines by use of the above model and comprehensive gear measurements;

- Enhance measurement machine and controls architecture and sensor hardware and software technologies to achieve submicron level accuracies in gear measurements;

- Develop statistical methods using measurement redundancies and replications to enhance measurement accuracies and to estimate measurement uncertainties;

- Develop computation algorithms and software to compensate for systematic machine-component errors and minimize final measurement inaccuracies;

- Develop procedures and artifacts adequate to verify submicron level accuracies in precision gear measurement;

- Verify the achieved level of gear measurement accuracy by implementing the above developments into an enhanced generative gear measurement machine.

Progress

A number of developments in hardware and software were necessary to achieve these goals.

QUALITY THAT IS BEYOND PRECISION

Apache AH-64 Main
Rotor Transmission



- Bevel
- Spur
- Helical
- Pinions
- Curvic couplings

52 years of excellence in flight-critical aerospace components, manufacturing AGMA 14 quality gears and pinions.

In-house multi-axis CNC/DNC machining, CAD/CAM center, computerized testing, metallurgical analysis. Purdy is compliant with MIL-Q-9858A and Boeing D1-9000.

The Purdy Corporation • 586 Hilliard Street
Manchester, CT 06040
Tel: (860) 649-0000 Fax: (860) 645-6293
www.purdytransmissions.com

CIRCLE 150



NEW versatile, accurate, economical Hob & Cutter Measuring Instrument

The base instrument in this new series is designed to measure rake of flute, radial or hook, and parallelism (includes indicator stand). Option for inspecting index spacing (includes index paw mechanism with tooling—precision arbor and index plates), using new index plates or your existing 6" ITW or 10" Barber Colman index plates.

NOW offering complete sharpening and coating services for hobs to 6". Straight gash. Inspection, sharpening, inspection—the best way for you to attain dramatic improvement in your gear quality.



Contact us today for specifications, pricing

<http://www.geartechology.com>

For specifications call (630) 377-2496 or Fax (630) 377-2546
MANUFACTURED GEAR & GAGE, INC.
P. O. BOX 7155, ELGIN, IL 60121

SEE US AT AGMA GEAR EXPO BOOTH #721

CIRCLE 164

TWO IN A SERIES

Boost Gear Performance WITHOUT CHANGING GEAR DESIGN



Want to make your customers sit up and take notice? Just add these bullets to your next gear ad. **Longer life. Improved torque at low temperatures. Extended lube intervals. Higher load-carrying capability.** Delivering these performance advantages is easy with the new Synthetic Gear Oil 340 Series from Nye Lubricants. Compatible with petroleum, plastics, and elastomers, they ensure less friction, less wear, less energy consumption, less maintenance, and longer gear life. Choose from one of three AGMA grades, and add Nye's SGO 340 Series to your gear boxes. No seal replacement is necessary. Then, roll out your new and improved gears — without going back to the drawing board. For technical data or samples, call Nye today.

Nye[®]
LUBRICANTS

PO Box 8927
New Bedford, MA 02742-8927
Phone: 508-996-6721
Fax: 508-997-5285
E-Mail: techhelp@nyelubricants.com

Technical Insight

SEE US AT AGMA GEAR EXPO BOOTH #330

CIRCLE 170

EXACT & REPEATABLE GEAR DATA

TRUE PITCH DIAMETER
TOTAL INDICATED READOUT
TRUE POSITION
CONCENTRICITY
ALL IN ONE GAUGE



No set-up or master required. PC based SPC program available or RS-232 port. Precision Tungsten Carbide balls or pins for maximum accuracy. Robust construction—Each gauge custom built. Over/under digital display w/ inch or mm conversion.

PHONE OR FAX FOR BROCHURE OR DEMO

DIGITAL
INTERFACE
GEAR
INSPECTION
TERMINAL

DIGIT

Member of AGMA

P.O. Box 367 • Springboro, OH 45066 • Fax: 513/746-5103
Phone: 513/746-3800 • E-mail: digit@erinet.com

SEE US AT AGMA GEAR EXPO BOOTH #334

CIRCLE 157

40 GEAR TECHNOLOGY

INDUSTRY NEWS

Environmental Chamber.

An environmental chamber was installed in the first year of the project. This room has been certified traceable to NIST to control temperature within .1°F and humidity under 45%. It has been used both to determine current day gear measurement machine accuracies and to provide the necessary environment to achieve project goals.

Enhanced Accuracy for Linear and Rotary Axes.

M & M and Penn State worked together to develop models to characterize the systematic machine and component errors throughout the entire system. Software to enhance probe locations in the light of these errors (slide path, yaw, and distance errors) were integrated into the M & M 9000 gear measurement program. Rotary axis errors were derived from a set of index measurements on a set of master gears. Software separated the gear index errors used in the measurements from the rotary axis errors. The M&M 9000 can calibrate index errors on a master gear to better than 15 microinches of measurement uncertainty.

Laser Linear Measuring System.

A laser linear measuring system was also developed. This system was evaluated by the Mid-Scale & Complex Form Metrology Group at NIST and shown to achieve a .2 micrometer (2 sigma) uncertainty for 800 mm displacement.

Gear Artifacts. To evaluate the enhanced measuring system with the lowest measurement uncertainties possible for profile, index and tooth alignment (lead), arti-

**M&M HAS
CONTRIBUTED
OVER
\$1 MILLION
TO THE GEAR
METROLOGY
RESEARCH
PROJECT.**

facts were designed and calibrated. NIST and the Oakridge Metrology Center Y-12 Plant measured a pin master, a 1" sphere master (under 2 microinch form errors), a lead master and an involute master. Procedures are currently being documented along with mathematical estimates of the final measurement uncertainties for all artifacts.

Final results of the research are currently being documented for NIST. Integration of this new technology into available products is underway at M & M. ⚙

Tell Us What You Think . . .

If you found this article of interest and/or useful, please circle 209.

For more information about M & M Precision Systems, circle 210.